

Compensation and extension cables
available with fast delivery

✓ 24h dispatch within 24h ✓ dispatch within 5-8 working days

Insulation	No. of conductors x cross section	Outer dimension	Conductor material and color coding acc. To IEC 584-3							
			JX	KX	KCA	KCB	EX	NX	TX	RCA
JJ oval insulation polyvinyl chloride PVC (-10...+105°C)	2x0.22mm ² (7x0.2)	3x4mm	✓	✓		✓	✓	✓	✓	✓
	2x0.44mm ² (13x0.2)	3x5mm	✓	✓		✓	✓	✓	✓	✓
	2x0.75mm ² (23x0.2)	4x6mm	✓	✓		✓		✓	✓	✓
	2x1.00mm ² (32x0.2)	4x6mm	✓	✓		✓			✓	✓
	2x1.30mm ² (40x0.2)	5x7mm		✓		✓			✓	
JJ insulation polyvinyl chloride PVC (-10...+105°C)	2x0.22mm ² (7x0.2)	Ø4mm	24h ✓	✓	24h ✓	✓		24h ✓	24h ✓	
	2x0.44mm ² (13x0.2)	Ø5mm	✓	✓		✓		✓	✓	✓
	2x0.75mm ² (23x0.2)	Ø6mm	✓	✓		✓				
JFJ insulation polyvinyl chloride PVC with alu-foil screen (-10...+105°C)	2x0.22mm ² (7x0.2)	Ø4mm	24h ✓	24h ✓		✓	24h ✓	24h ✓	24h ✓	24h ✓
	2x0.44mm ² (13x0.2)	Ø5mm	✓	✓		✓	✓	✓	✓	✓
	2x0.75mm ² (23x0.2)	Ø6mm	✓	✓		✓		✓	✓	✓
TT oval insulation teflon® PFA (-75...+260°C)	2x0.22mm ² (7x0.2)	2x3mm	✓	✓			✓	✓	✓	✓
TFT insulation teflon® PFA, with alu-foil screen (-75...+260°C)	2x0.22mm ² (7x0.2)	Ø3mm	✓	✓			✓	✓	✓	✓
	2x0.44mm ² (13x0.2)	Ø4mm	✓	✓				✓	✓	✓
TCuT insulation teflon® FEP, with tin-platted copper braid (-75...+205°C)	2x0.22mm ² (7x0.2)	Ø3mm	✓	✓	24h ✓				✓	
	4x0.22mm ² (7x0.2)	Ø3mm			24h ✓					
	2x0.50mm ² (7x0.3)	Ø4mm			24h ✓					
	4x0.50mm ² (7x0.3)	Ø5mm			24h ✓					
TP insulation teflon® PFA with outer steel braid (-75...+260°C)	2x0.13mm ² (7x0.15)	2x2mm	✓	✓					✓	
GLGLP oval insulation fiberglass, outer stainless steel braid (up to +400°C)	2x0.22mm ² (7x0.2)	3x4mm	✓	✓				✓	✓	✓
	2x0.44mm ² (13x0.2)	3x4mm	✓	✓					✓	✓
	2x0.75mm ² (23x0.2)	4x5mm	✓	✓				✓	✓	✓
	2x1.00mm ² (32x0.2)	4x5mm	✓	✓					✓	✓
	2x1.30mm ² (40x0.2)	4x6mm		✓						✓
SLSL insulation silicone rubber (-60...+180°C)	2x0.50mm ² (7x0.3)	Ø7mm		✓		✓			✓	✓
	2x1.50mm ² (19x0.3)	Ø8.5mm				✓			✓	✓

Compensation and extension cables
available with fast delivery

✓^{24h} dispatch within 24h ✓ dispatch within 5-8 working days

Insulation	No. of conductors x cross section	Outer dimension	Conductor material and color coding acc. To IEC 584-3							
			JX	KX	KCA	KCB	EX	NX	TX	RCA
TSL insulation silicone rubber (-60..+180°C)	2x0.22mm ² (7x0.2)	Ø4mm	✓ ^{24h}		✓ ^{24h}				✓ ^{24h}	
SLCuSL insulation silicone rubber, with inner copper braid (-60..+180°C)	2x0.22mm ² (7x0.2)	Ø5mm		✓						✓
	2x0.50mm ² (7x0.3)	Ø7.5mm	✓	✓		✓			✓	✓
	2x1.50mm ² (19x0.3)	Ø9mm		✓		✓				✓
SLSLP insulation silicone rubber, outer steel braid (-60..+180°C)	2x0.50mm ² (7x0.3)	Ø6.6mm			✓ ^{24h}					
	4x0.50mm ² (7x0.3)	Ø7mm			✓ ^{24h}					
	6x0.50mm ² (7x0.3)	Ø7.5mm			✓ ^{24h}					

Updated: 2019-06-13

You have not found the right product for your application?

- Use the Product Configurator and send us your enquiry – we will reply with quotation quickly
- Call to us +48 71 3115860 (Monday to Friday from 7:00 to 15:00 CET) – we will advice and check availability of cables that are not on the list above.

